AMENDMENTS TO THE CLAIMS

The Office Action indicates that claims 1-2, 5, 7-11, and 15-18 are pending.

Claims 1, 2, 15, 17, and 18 are herein amended as set forth in the following listing of claims that

will replace all prior versions and listings of claims in this application.

Listing of Claims:

1. (currently amended) A communication apparatus which receives image data taken by an

imaging apparatus connected through a network, comprising:

a storage unit for storing ~~control~~ preset parameter information to control at least one

operation of panning, tilting, zooming and irising of said imaging apparatus;

a first output unit for outputting to a display unit a first synthetic map image which is

obtained by synthesizing a camera symbol indicating a setting location of said imaging apparatus

on a map image;

a selection unit for selecting an imaging apparatus to be controlled in accordance with

designating the camera symbol corresponding to the imaging apparatus on the first synthetic map

image;

[[an]] a second output unit for outputting to a display unit a second synthetic map image

which is obtained by synthesizing a first symbol corresponding to the ~~control~~ preset parameter

information of the selected imaging apparatus stored in said storage unit[[,]] on [[a]] the first

synthetic map image ~~indicating a setting location of said imaging apparatus~~, and a second

symbol corresponding to the ~~control~~ preset parameter information of the selected imaging

apparatus stored in said storage unit which has same identifying information of preset parameter

as an identifying information of preset parameter of the first symbol on a different area from the

930350 v1

map after an imaging apparatus is selected by said selection unit;

an instruction unit for permitting [[a]] said user to instruct selectively the first symbol on

the map and the second symbol on the different area which have same identifying information of

preset parameter, displayed by said display unit;

a transmit unit for transmitting the ~~control~~ preset parameter information to control at least

one operation of ~~paning~~ panning, tilting, zooming, and irising of said imaging apparatus stored

by said storage unit to the imaging apparatus in response to an instruction of at least one of the

first symbol and the second symbol on the map by said instruction unit.

2. (Currently amended) An apparatus according to Claim 1, wherein there are the plural ~~control~~

preset parameter information stored by said storage unit, and the plural first symbols

corresponding to the plural control information are synthesized on the first synthetic map image.

Claims 3-4. (canceled)

5. (previously presented) An apparatus according to Claim 1, wherein the image data changed

by controlling said imaging apparatus is displayed on said display unit, and said storage unit

stores as the control information the operation state of said imaging apparatus when an

instruction was given by said instruction device.

Claim 6 (canceled)

7. (previously presented) An apparatus according to Claim 1, wherein said storage unit stores a

title corresponding to the control information.

8. (previously presented) An apparatus according to Claim 7, wherein said output unit also

outputs the title to said display unit.

930350 v1

Application No. 09/619,876
DOCKET: 1232-4636   PATENT

9. (previously presented) An apparatus according to Claim 8, wherein the title is output

according as an instruction image of an instruction device is moved onto the first symbol.

10. (original) An apparatus according to Claim 1, wherein the control information is deleted

according to a deletion instruction from an instruction device.

11. (original) An apparatus according to Claim 5, wherein there are said plural imaging

apparatuses, and the control information can be instructed to each of said imaging apparatuses.

Claims 12-14. (canceled)

15. (currently amended) An apparatus according to Claim 1, wherein a synthesizing position can

be arbitrarily designated when the first symbol is synthesized to the first synthetic map image.

16. (previously presented) An apparatus according to Claim 1, wherein said storage unit stores a

synthesizing position corresponding to the control information.

17. (currently amended) A control method of a communication apparatus which receives image

data taken by an imaging apparatus connected through a network, comprising the steps of:

        storing control information to control at least one operation of panning, tilting, zooming,

and irising of the imaging apparatus;

        outputting to a display unit a first synthetic map image which is obtained by synthesizing

a camera symbol indicating a setting location of said imaging apparatus on a map image;

        selecting an imaging apparatus to be controlled in accordance with designating the

camera symbol corresponding to the imaging apparatus on the first synthetic map image;

        outputting to a display unit a second synthetic map image which is obtained by

synthesizing a first symbol corresponding to the ~~control~~ preset parameter information of the

930350 v1

selected imaging apparatus stored in said storage step[[,]] on [[a]] the first synthetic map image

~~indicating a setting location of the imaging apparatus~~, and a second symbol corresponding to the

~~control~~ preset parameter information of the selected imaging apparatus stored in said storage step

which has same identifying information of preset parameter as an identifying information of

preset parameter of the first symbol on a different area from the map after an imaging apparatus

is selected by said selecting step;

utilizing an instruction unit for permitting [[a]] said user to instruct selectively the first

symbol on the map and the second symbol on the different area which have same identifying

information of preset parameter, displayed by said display unit; and

transmitting the ~~control~~ preset parameter information to control at least one operation of

panning, tilting, zooming, and irising of said imaging apparatus stored in said storage step to the

imaging apparatus in response to an instruction of at least one of the first symbol and the second

symbol on the map by said unit.

Claim 18. (currently amended) A storage medium which stores a program to be executed by a

computer for controlling an imaging apparatus in a communication apparatus which receives

image data taken by the imaging apparatus connected through a network, said program

comprising:

a code of storing control information to control at least one operation of panning, tilting,

zooming, and irising of the imaging apparatus;

a code of outputting to a display unit a first synthetic map image which is obtained by

synthesizing a camera symbol indicating a setting location of said imaging apparatus on a map

image;

a code of selecting an imaging apparatus to be controlled in accordance with designating

5 of 11

the camera symbol corresponding to the imaging apparatus on the first synthetic map image;

a code of outputting to a display unit a second synthetic map image which is obtained by

synthesizing a first symbol corresponding to the ~~control~~ preset parameter information of the

selected imaging apparatus stored in said storage step[[,]] on [[a]] the first synthetic map image

~~indicating a setting location of the imaging apparatus~~, and a second symbol corresponding to the

~~control~~ preset parameter information of the selected imaging apparatus stored in said storage step

which has same identifying information of preset parameter as an identifying information of

preset parameter of the first symbol on a different area from the map after an imaging apparatus

is selected by said selecting step;

a code of utilizing an instruction unit for permitting [[a]] said user to instruct selectively

the first symbol on the map and the second symbol on the different area which have same

identifying information of preset parameter, displayed by said display unit; and

a code of transmitting the ~~control~~ preset parameter information to control at least one

operation of panning, tilting, zooming, and irising of said imaging apparatus stored by said

storage code to the imaging apparatus in response to an instruction of at least one of the first

symbol and the second symbol on the map by said instruction unit.

930350 v1